

LED Medical Lighting

FEATURES: 94 CRI • 4700 Color Temperature

GALAXY Spring Arm




Mount	Arm Reach	Typical Working Distance	Light Intensity	Spot Size	Part No.
Ceiling	60 in.	28 in.	60,000	10"	4x3-GS1
Ceiling Dual	60 in.	28 in.	60,000	10"	4x3-GS2



Mount	Arm Reach	Typical Working Distance	Light Intensity	Spot Size	Part No.
Ceiling	60 in.	28 in.	115,000	12"	9x3-GS1
Ceiling Dual	60 in.	28 in.	115,000	12"	9x3-GS2

GALAXY Balance Arm



Mount	Arm Reach	Typical Working Distance	Light Intensity	Spot Size	Part No.
Ceiling	60 in.	28 in.	60,000	10"	4x3-GB1
Ceiling Dual	60 in.	28 in.	60,000	10"	4x3-GB2
Ceiling	60 in.	28 in.	115,000	12"	9x3-GB1
Ceiling Dual	60 in.	28 in.	115,000	12"	9x3-GS2

Other members of the StarTrol LED family:



Distributed by:

StarTrol.com

Products are subject to improvements/changes without notice.
Form #: SAMAGAL001 Rev. 0



Huot Instruments, LLC
N59 W14508 Bobolink Ave
Menomonee Falls, WI 53051



LED Medical Lighting



Galaxy
SERIES



StarTrol.com



Made in the U.S.A.



The Galaxy Series

Minor Surgical and Examination Lighting

The Galaxy features a new ceiling pole configuration:

- ★ The primary pivot points feature unlimited rotation
- ★ Available in a “Spring Arm” or “Balance Arm”

StarTrol™ LED Medical Lights produce a bright white light, (94 CRI and 4700K), ideal for true color rendition.

Our lights are cool and comfortable to work under, with virtually no radiant heat being generated by the LED's.

StarTrol™ lights are energy efficient, using less than one-third the energy of a halogen light, and require minimal maintenance.

StarTrol™ LED Medical Lights are durable, precision machined and feature a stellar 10-year warranty.

Proudly made in the United States of America.

Spring Arm: 4x3-GS1 (Single)



Balance Arm: 9x3-GB1 (Single)

Balance Arm: 4x3-GB1 (Single) also available



Spring Arm: 9x3-GS2 (Dual)



StarTrol™ features:

- Energy Efficient & Eco-friendly
- Bright, natural white light
- 10-year limited warranty
- Cool to work under
- 40,000 hours of LED life
- Infinite variable positioning
- Multi-level dimming

Spring Arm: 9x3-GS1 (Single)



Spring Arm: 4x3-GS2 (Dual)

