

Tom 2 Pediatric Crib



Improving patient and caregiver safety, while enhancing the patient experience

Introducing Tom 2





Improved patient and



INNOVATIVE FALL PREVENTION

- Innovative top rail roller bar technology replaces the need for an enclosed canopy
- Top rail roller bar, telescopic siderails, bed exit alarm and low bed height work together as part of a fall prevention protocol to provide maximum patient safety

ENHANCED PATIENT ACCESS

- Telescopic siderails with five height positions provide a customizable solution for safe and easy access to the child
- Siderail door allows easy access to pumps and lines when the patient is sleeping
- Transparent, removable bed ends provide visibility and 360 degree access to the patient



caregiver safety



IMPROVED MONITORING

- Built-in scale allows the caregiver to monitor the patient's weight, even while they are sleeping
- Multi-zone bed exit alarm helps monitor the patient's position and protect against patient falls

BETTER CARE ENVIRONMENT

- Smooth and quiet autoregression maintains a safe in-bed environment for the patient as the backrest is raised and lowered
- Fully electric positioning allows the caregiver to easily raise the bed to an ergonomic position for providing care and lower the bed to a safe height for the patient



Enhanced patient experience





- Transparent bed ends provide the patient with a full view of their surroundings, allowing parents and caregivers to have unobstructed visibility of the child
- Fully electric functionality allows caregivers to quietly operate the bed without disturbing the child
- Colorful designs reflect the playful world of children and enhance the experience for the patient



Tom 2 at a glance

- Integrated IV pole
- Manual CPR
- 3 Accessory rails
- Patient access door
- Oxygen tank holder
- 6 Central brakes
- Accessory/IV pole holders
- 8 Scale (Optional)
- 9 Accessory box
- Accessory control panel



TECHNICAL SPECIFICATIONS

External dimensions	62 x 33 in
Recommended mattress dimensions	56 x 28 x 4 in
Safe working load	165 lb
Mattress platform height (min-max) (electrically adjusted)	23 - 33 in
Trendelenburg/Reverse Trendelenburg tilt (electrically adjusted)	15°/15°

Max. height of siderail	32 in
Autoregression of backrest	4 in
Maximum gap between backrest and head end	1 in
Weight (depending on equipment)	298 lb
Maximum backrest angle (electrically adjusted)	40°
Central caster brake and steering	Yes

