

protevo GTE

Convertible Alternating Pressure Air Surface



Convertable Prevention and Treatment

ProtevoTM GTE is an advanced pressure redistribution mattress that provides flexible therapy to help you meet the wound care needs of your patient. Used without the control unit, Protevo GTE provides reactive pressure redistribution through self adjusting air cells. Easily convert the surface with an optional control unit to provide alternating pressure therapy.

Protevo. Protecting patients with wound care that evolves to meet their needs.


Protevo GTE – convertible alternating pressure air surface

Highlights

- 3-dimensional, sculpted envelopment layer increases patient comfort and assists in the reduction of pressure ulcer incidence
- 4-way stretch top cover helps minimize sher and friction
- Ten air cells absorb and displace patient weight
- Mattress can be used without control unit as a self-adjusting, static air surface
- Alternating pressure therapy provided in 10 minute cycle time
- 550 lbs maximum patient weight
- Dedicated heel zone featuring 2 air cylinders and visco-elastic foam pillow



The Protevo GTE mattress can be used with any flat deck frame. When used with a LINET bed, the Protevo GTE mattress works in combination with the Ergoframe® design of the bed to help maintain patient position, neutralize shear and minimize pressure in the sacral area. This leads to improved patient comfort and easier and safer nursing care.







Protevo GTE Construction

- Ten air cells directly beneath visco-elastic comfort layer
- Overall mattress height: 8 inches
 - Bottom layer: 1 inch
 - Air Cells: 4-1/2 inches
 - Comfort layer: 2-1/2 inches
- Comfort layer spans entire length and width of mattress
- Side bolster foam for support

- 5 degree heel slope
- 4-way stretch top cover (replaceable)
- Non-slip mattress bottom
- Provides self-adjusting, advanced pressure redistribution without a control unit
- Converts to alternating pressure mattress with optional control unit; 10 minute cycle time
- Standard 5-year warranty

